

M-710iC/50T



Max. load capacity at wrist: 50 kg




Max. reach: 1900 mm

FANUC


Robot			Max. load capacity at wrist (kg)	Reach (mm)	Controlled axes	Repeatability (mm)	Mechanical weight (kg)	Motion range (°)						Maximum speed (°/s)						J4 Moment/ Inertia	J5 Moment/ Inertia	J6 Moment/ Inertia	Average Power consumption (kW)	Protection	
Series	Version	Type						J1	J2	J3	J4	J5	J6	J1	J2	J3	J4	J5	J6					Body standard/optional	Wrist & J3 arm standard/optional
M-710	iC	50T	50	1900 ^{*1}	6	± 0.07	410	*1	261	491	720	250	720	*1	175	175	250	250	355	206/28	206/28	127/11	2.5	IP54/ IP67	IP67

● standard ○ on request - not available *1 depending on rail specification

M-710iC/50T Top mount



M-710iC/50T



MOTION CONTROLS ROBOTICS
 1500 Walter Ave, Fremont, OH 43420

Authorized FANUC SYSTEM INTEGRATOR
 CERTIFIED SERVICE PROVIDER

Contact Sales
 419.334.5886
 sales@mcri-us.com
 Click for a quote
 motioncontrolsrobotics.com